

Change of crackling noise in granite by thermal damage: Monitoring nuclear waste deposits

**KAINAN XIE^{1,2}, XIANG JIANG^{1,3,4,*}, DEYI JIANG¹, YANG XIAO³, SHIWAN CHEN⁵, KARIN A. DAHMEN⁶,
EDUARD VIVES², ANTONI PLANES², AND EKHARD K.H. SALJE^{4,7}**

¹State Key Laboratory of Coal Mine Disaster Dynamics and Control, Chongqing University, Chongqing 400044, P.R. China

²Departament de Física de la Matèria Condensada, Facultat de Física, Universitat de Barcelona, Martí i Franquès, 1, 08028 Barcelona, Catalonia

³College of Civil Engineering, Chongqing University, Chongqing 400045, P.R. China

⁴Department of Earth Sciences, University of Cambridge, Cambridge CB2 3EQ, U.K.

⁵College of Resources and Environment Engineering, Guizhou University, Guiyang, 550025, P.R. China

⁶Department of Physics, University of Illinois at Urbana Champaign, Urbana, Illinois 61801, U.S.A.

⁷State Key Laboratory for Mechanical Behaviours of Materials, Xi'an Jiao Tong University, Xi'an 710049, P.R. China

ABSTRACT

High-sensitivity detection of acoustic emission from granite under uniaxial stress, together with advanced statistical analysis, shows changing collapse mechanisms when a sample is pre-heated. Massive microstructural changes occur at temperatures >500 °C while low-temperature ($<<500$ °C) treatment leads to scale invariant crackling noise with a mixed fix-point behavior. After treatment at higher temperatures, the collapse occurs via acoustic signals that show energy distributions with systematic deviations from the Gutenberg-Richter law while the Omori's and Båth's laws are not influenced by the thermal treatment. The granite samples stem from the site in the Beishan mountains where a new burial site for nuclear waste will be constructed. According to the 13th Five-Year Plan of the P.R. China, Chinese nuclear power installed capacity will reach 58 million kilowatts in 2020 and produce about 3200 tons of high-level nuclear waste every year. Monitoring the stability of the host rock at high temperatures becomes hence a key issue. Our analysis can serve as a blueprint for a protocol for continuous monitoring of the burial site.

Keywords: Crackling noise, granite, thermal damage, acoustic emission